

CLEAR CLOGS QUICKLY & EASILY; MAXIMIZE PRODUCTIVITY



FEATURES AND BENEFITS

- Simply rotate handle 180° and blow obstructions out of the opening in the back of the tip – it's fast and easy
- Tungsten carbide orifice provides maximum erosion resistance for high-pressure spraying
- Easy to replace the orifice – no need to disassemble
- Guard safety feature

SPECIFICATIONS:

Maximum pressure: 5000 psi (345 bar)

Spray pattern: Flat spray

Materials: Stainless steel holder with tungsten carbide orifice insert and protective nylon lugs



IDEAL FOR:

- Manual spraying
- High-pressure paint spraying
- Road paint striping
- Fiberglass manufacturing

ORDERING INFORMATION

ROTOCLEAN AIRLESS SPRAY NOZZLES

RotoClean
Number

+

Orifice/Handle
Insert Kit

Example

AA225 – 6

+

26081-813



PERFORMANCE DATA: ROTOCLEAN AIRLESS SPRAY NOZZLES

For 225 Handle/Orifice Insert No. 26081-	Equiv. Orifice Dia. (in.)	Flow Rate Capacity* (gallons per minute)				Approx.** Spray Pattern Width (in.) at 1 ft. distance
		500 psi	1000 psi	1500 psi	2000 psi	
813	.013	.09	.12	.15	.18	16-1/2
815	.015	.12	.16	.20	.23	17
918	.018	.18	.25	.30	.36	19
1021	.021	.24	.33	.41	.47	21
1023	.023	.28	.40	.49	.57	22
1126	.026	.35	.50	.61	.72	23
611	.011	.06	.08	.10	.12	13
713	.013	.09	.12	.15	.18	14
715	.015	.12	.16	.20	.23	15
818	.018	.18	.25	.30	.36	17
921	.021	.24	.33	.41	.47	19
923	.023	.28	.40	.49	.57	19
1026	.026	.35	.50	.61	.72	21
1031	.031	.53	.75	.91	1.1	21
1036	.036	.71	1.0	1.2	1.4	22
511	.011	.06	.08	.10	.12	11-1/2
613	.013	.09	.12	.15	.18	12-1/2
615	.015	.12	.16	.20	.23	13
718	.018	.18	.25	.30	.36	15
821	.021	.24	.33	.41	.47	17
823	.023	.28	.40	.49	.57	17
926	.026	.35	.50	.61	.72	19
931	.031	.53	.75	.91	1.1	19
936	.036	.71	1.0	1.2	1.4	19
513	.013	.09	.12	.15	.18	10-1/2
515	.015	.12	.16	.20	.23	11
***	.017	.16	.22	.27	.31	12-1/2
618	.018	.18	.25	.30	.36	13
***	.019	.19	.28	.34	.39	13
721	.021	.24	.33	.41	.47	15
723	.023	.28	.40	.49	.57	15
726	.026	.35	.50	.61	.72	16
731	.031	.53	.75	.91	1.1	16
736	.036	.71	1.0	1.2	1.4	16
411	.011	.06	.08	.10	.12	8-1/2
413	.013	.09	.12	.15	.18	9
415	.015	.12	.16	.20	.23	10
***	.017	.16	.22	.27	.31	10-1/2
518	.018	.18	.25	.30	.36	11
***	.019	.19	.28	.34	.39	11

For 225 Handle/Orifice Insert No. 26081-	Equiv. Orifice Dia. (in.)	Flow Rate Capacity* (gallons per minute)				Approx.** Spray Pattern Width (in.) at 1 ft. distance
		500 psi	1000 psi	1500 psi	2000 psi	
621	.021	.24	.33	.41	.47	12
623	.023	.28	.40	.49	.57	13
626	.026	.35	.50	.61	.72	14
631	.031	.53	.75	.91	1.1	14
636	.036	.71	1.0	1.2	1.4	14
311	.011	.06	.08	.10	.12	7-1/2
313	.013	.09	.12	.15	.18	8
***	.017	.16	.22	.27	.31	9-1/2
418	.018	.18	.25	.30	.36	10
***	.019	.19	.28	.34	.39	10
521	.021	.24	.33	.41	.47	11
523	.023	.28	.40	.49	.57	11
526	.026	.35	.50	.61	.72	12
***	.029	.46	.65	.80	.92	12
531	.031	.53	.75	.91	1.1	12
536	.036	.71	1.0	1.2	1.4	12
315	.015	.12	.16	.20	.23	7
318	.018	.18	.25	.30	.36	7
***	.019	.19	.28	.34	.39	7
421	.021	.24	.33	.41	.47	8
423	.023	.28	.40	.49	.57	8-1/2
426	.026	.35	.50	.61	.72	9
431	.031	.53	.75	.91	1.1	9
436	.036	.71	1.0	1.2	1.4	9
211	.011	.06	.08	.10	.12	5
213	.013	.09	.12	.15	.18	5
215	.015	.12	.16	.20	.23	5-1/2
***	.017	.16	.22	.27	.31	6
321	.021	.24	.33	.41	.47	6-1/2
323	.023	.28	.40	.49	.57	7
326	.026	.35	.50	.61	.72	7
331	.031	.53	.75	.91	1.1	7
336	.036	.71	1.0	1.2	1.4	7
218	.018	.18	.25	.30	.36	5
221	.021	.24	.33	.41	.47	5-1/2
223	.023	.28	.40	.49	.57	5-1/2
226	.026	.35	.50	.61	.72	6
231	.031	.53	.75	.91	1.1	6
236	.036	.71	1.0	1.2	1.4	6

* Tabulated capacities based on water.


** Spray pattern width is based on liquid with viscosity of 20 seconds, #4 Zahn Cup spraying at 1600 psi (110 bar). Coverage will vary with viscosities and pressures.

*** Available on special request.



ROTOCLEAN® AIRLESS SPRAY NOZZLES

DIMENSIONS AND WEIGHTS

	Nozzle	A (in.)	B (in.)	Net Weight (oz.)
	225	2.437	2	4.2

Based on largest/heaviest version of each type.

COMPATIBLE SPRAY GUNS

RotoClean No.	Connection Thread Size	Gasket No.	Compatible Spray Gun
225-2	11/16"-16	7894-NY	SPRAYING SYSTEMS CO. 24 AUA AND GRACO
225-3	3/4"-16	19078-NY	BALCRANK
225-6	7/8"-14	11918-NY	GRACO
225-8	3/8" NPS	12552-NY	NORDSON
225-9	3/8" NPS	10660-NY	DEVILBISS
225-10	3/4"-20	19079-NY	BINKS 50
225-11	M18 x 1 Metric	7894-NY	ATLAS COPCO
225-12	3/8" NPS	7894-NY	SPEE-FLO
225-13	M18 x 1 Metric	7894-NY	DEICKE & KOPPERSCHMIDT
225-14	1-14	9632-NY	SPRAYING SYSTEMS CO. 44 AUA
225-15	11/16"-16	12552-NY	BINKS 43
225-16	5/8"-14 BSPP	11918-NY	—
225-17	11/16"-16	13358-NY	WAGNER
225-18	M18 x 1.5 Metric	7894-NY	—

